

HOTBODIES RACING.COM

08' HAYABUSA UNDERTAIL INSTRUCTIONS

HOTBODIES RACING RECOMMENDS THAT YOU HAVE A PROFESSIONAL MECHANIC PERFORM THIS INSTALLATION. IF YOU CHOOSE TO "DO-IT-YOURSELF" ALWAYS TAKE APPROPRIATE SAFETY MEASURES WHEN INSTALLING THIS PRODUCT. CAREFULLY READ ALL INSTRUCTIONS BEFORE BEGINNING THE INSTALLATION PROCESS!



1) Remove solo seat cowl, and unclip license plate wires from harness. Remove 10mm mudflap bolts located underneath tail section. Remove mudflap assembly and re-install mudflap bolts to secure batterybox.



2) Remove four pop rivets along tail section including all mounting bolts for tail section. This will allow tail section to move freely, making installation of undertail simple.



3) Wire in license plate light. On undertail the red wire goes to the brown wire on the bike, and the black wire goes to the black and white tracer on the bike.



4) Slide new undertail in place and mount with supplied screw rivets.

Note: Stock pop rivets may also be used to secure undertail
Reinstall and tighten all hardware and your done!

READ CAREFULLY BEFORE INSTALLATION! This undertail like all undertails has been designed for off road racing use only, and has not been presented for D.O.T. certification! Hotbodies Racing Inc., our distributors, and our dealers will NOT be responsible for the use or misuse of this product. Always check with your local Department of Motor Vehicles before modifying any aspect of your motorcycle.